

Article No. :	01070001-EZLock		
Product name :	BZU/1 EZ 12-000+S5 DG 3.5MM		
皮带类型 :	PU - EZLock皮带	Product group :	PU - EZLock Belt
皮带编码 :	EZLock	Product code :	EZLock

皮带组成
布层

布层材料 :	聚酯
布层数量 :	1
布层特性 :	横向稳定

上层

涂层材料 :	PU
颜色 :	深绿色
硬度 :	90° Shore A
表面 :	S5

下层

涂层材料 :	EZLock
颜色 :	白色
硬度 :	-
表面 :	EZLock

Product Configuration
Fabric

Type of fabric :	Polyester
Number of Fabrics :	1
Fabric feature :	Laterally stiff

Top side

Coating material :	PU
Colour :	Dark Green
Hardness :	90° Shore A
Surface :	S5

Bottom side

Coating material :	EZLock
Colour :	White
Hardness :	-
Surface :	EZLock

技术资料

总厚度 :	3.5 mm
重量 :	3.5 Kg/m ²
温度 :	-30° C / +100° C
与钢材的摩擦系数 :	0.327

1% 拉伸 :	12 N/mm
抗静电 :	否
阻燃 :	否

最小转弯直径 :	80 mm
背部最小转弯直径 :	-

最大生产宽度 :	2000 mm
标准宽度 :	3000 mm

注意事项 / Others:

安装时张力至少设定为 0.3%
Installation tension should be min. 0,3%.

其他 / Additional Features:

食品级. / Food Approved.

接头信息 / Jointing Technical Info:

上温 / Upper platen Temp. :	-
下温 / Lower platen Temp. :	-
保温 / Curing time in press :	-
压力 / Pressure :	-

Technical Data

Total thickness :	3.5 mm
Weight :	3.5 Kg/m ²
Temperature :	-30° C / +100° C
Coef. Friction > Steel :	0.327

Tensile Force at 1 % elongation:	12 N/mm
Permanent antistatic:	No
Flame retardant :	No

Min. Pulley Ø :	80 mm
Min back flex Ø :	-

Max. production width :	2000 mm
Standard Width :	3000 mm

All informations are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Ino Industrial Belting Co., Ltd has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences.

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.

www.inobelts.com
info@inobelts.com