

品号：	-
产品名称：	滚轮带
皮带类型：	PU - 滚轮带
皮带编码：	

Article No.:	-
Product name:	PU Roller Driving Belt
Product group:	PU Roller Driving Belt
Product code:	

**皮带组成**
**布层**

布层材料：	尼龙
布层数量：	1
布层特性：	横向柔软

**上层**

涂层材料：	PU
颜色：	蓝色
硬度：	90° Shore A
表面：	S5

**下层**

涂层材料：	0
颜色：	深绿色
硬度：	-
表面：	布层

**强力层**

材料：	Kevlar
颜色：	黄色
线数：	32根

**Product Configuration**
**Fabric**

Type of fabric:	Nylon
Number of Fabrics:	1
Fabric feature:	Flexible

**Top side**

Coating material:	PU
Colour:	Sky Blue
Hardness:	90° Shore A
Surface:	S5

**Bottom side**

Coating material:	0
Colour:	Dark Green
Hardness:	-
Surface:	Fabric

**Tension Member**

Material:	Kevlar
Colour:	Yellow
Number of cords:	32

**技术资料**

总厚度：	4.0 mm
重量：	4.5Kg/m <sup>2</sup>
温度：	-20° C / + 90° C
布面与钢材的摩擦系数：	0.33
花纹与钢材的摩擦系数：	0.35

1% 拉伸：	60 N/mm
防静电：	否
阻燃：	否

生产最大宽度：	-
标准宽度：	48~50 mm

**Technical Data**

Total thickness:	4.0 mm
Weight:	4.5Kg/m <sup>2</sup>
Temperature:	-20° C / + 90° C
Coef. Friction > Fabric vs Steel:	0.33
Coef. Friction > Profile vs Steel:	0.35

Tensile Force at 1% elongation:	60 N/mm
Permanent antistatic:	No
Flame retardant:	No

Max Production Width:	-
Standard Width:	48~50 mm

**注意事项 / Others:**

安装时张力至少设定为 0.3% / installation tension should be min. 0.3%.

**其他 / Additional Features:**

Logistics

All informations are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Ino Industrial Belting Co., Ltd has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences.

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.

www.inobelts.com  
info@inobelts.com