

## Product

# Datasheet

## BU/3 EM 20-00+04 M2 AS BK 2.6mm

**Article number**

BD-20TT

**Construction**

Product group	PU-Printing Blanket
Conveying side	
Surface structure	Matt
Coating material	0.4 mm
Colour	Black
Running side	
Surface structure	
Coating material	00 (Fabric impregnation)
Colour	-
Type of fabric	EM
Number of fabric plies	3

**Technical data**

Total thickness	2.6 mm
Weight	3.0 kg/m <sup>2</sup>
Force elongation at 1%	20 N/mm
Min. Pulley Ø	100 mm
Min. Pulley Ø with back flex	150 mm
Coefficient of friction against steel running side according to ISO 21182	0.25
Permissible temperature	-20°C/+90°C
Coating hardness	95 ShA
Antistatic	√
Standard Width	3000 mm

**Properties**

Lateral stiffness	√
Trough/Curve suitable	
Food grade (FG)	
REACH / ROHS	√
FDA	
EC1935:2004 / EU No.10/2011	
Anti-microbial and anti-hydrolysis (AM)	
Heat resistant (HR)	
Fray-less (FL)	
Flame-retardant (FR)	
Noise development	
Conductive (Ω)	
Oil resistant	√

**Jointing Technical Info**

Joint type	Finger Joint
Upper platen Temp.	170°C
Lower platen Temp.	162°C
Curing time	480 seconds
Pressure	2 bar(s)
Slider bed	
Rolling support	

**Disclaimer**

All informations are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Bode Belting GmbH has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences